



Laser Filter OD Values

Filter Number: 6001 UV, CO2

Stated coverage: OD 7+ @ 190-360, OD 7+ @ 5000-11000nm

Filter Color: Clear Approximate VLT 90%

Wavelength (nm)	OD	Wavelength (nm)	OD	Wavelength (nm)	OD
190	7+	570		940	
200	7+	580		950	
210	7+	590		960	
220	7+	600		970	
230	7+	610		980	
240	7+	620		990	
250	7+	630		1000	
260	7+	640		1010	
270	7+	650		1020	
280	7+	660		1030	
290	7+	670		1040	
300	7+	680		1050	
310	7+	690		1060	
320	7+	700		1064	
330	7+	710		1070	
340	7+	720		1080	
350	7+	730		1090	
360	7+	740		1100	
370	5	750		1110	
380	3.7	755		1120	
390	1	760		1130	
400	0.1	770		1140	
410	0.1	780		1150	
420		790		1160	
430		800		1170	
440		810		1180	
450		820		1190	
460		830		1200	
470		840		5000-11000	7+
480		850			
490		860			
500		870			
510		880			
520		890			
530		900			
540		910			
550		920			
560		930			

NOTE: OD values above are average values of representative lots of filters. They are not guaranteed minimums for every filter. KENTEK will certify minimum OD levels with markings on each product.

"Laser People Helping Laser People"[®]

THE KENTEK CORPORATION

1 Elm Street · Pittsfield, NH 03263 USA · (603) 435-7201 · Fax (603) 435-7441

E-mail: info@kenteklaserstore.com · Web Site: <http://www.kenteklaserstore.com>

Rev 10/06

© 2006